

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113612 A1

(51) International Patent Classification⁷: **D21H 21/44**

(21) International Application Number:
PCT/EP2004/006430

(22) International Filing Date: 15 June 2004 (15.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
VR2003A000079 20 June 2003 (20.06.2003) IT

(71) Applicant (for all designated States except US):
CARTIERE FEDRIGONI E C. S.P.A. [IT/IT]; Strada
del Linfano, 16, I-38062 Arco (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FEDRIGONI,
Giuseppe** [IT/IT]; Corso Porta Nuova, 41, 37122 Verona
(IT).

(74) Agent: **MODIANO, Guido**; Modiano & Associati, Via
Meravigli, 16, IT-20123 Milano (IT).


(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: SECURITY PAPER, PARTICULARLY FOR LABELS



(57) Abstract: A security paper (1), comprising a first and a second outer layers (2a, 2b) and at least one intermediate layer (3) that is interposed between the first and second outer layers, the first outer layer (2a) being coupled to the intermediate layer (3) so as to form a monolithic body, and the intermediate layer (3) having a different coloring with respect to the first (2a) and second (2b) outer layers.

WO 2004/113612 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SECURITY PAPER, PARTICULARLY FOR LABELS

Technical Field

The present invention relates to a security paper particularly but not exclusively suitable for marking food products.

5 Background Art

Currently the need is particularly felt to mark products, specifically food products such as meat, fish, et cetera, by means of labels or similar media that allow, by imprinting an abbreviation or a bar code, to trace the "history" of the product (country of origin, farm where the animal was
10 raised, date of birth and/or slaughter, location where slaughter took place, et cetera).

However, these labelings, and particularly the media on which these data must be imprinted, must have the characteristic of being difficult to duplicate and/or reproduce: in practice, they must be "forgery-proof" papers
15 in every respect, in order to prevent marketing of products that bear false labeling and whose origin would therefore be impossible to determine with certainty.

Disclosure of the Invention

The aim of the present invention is to provide a security paper,
20 particularly but not exclusively suitable for marking food products.

Within this aim, an object of the invention is to provide a security paper that allows to check its authenticity in a simple and straightforward manner.

Another object of the security paper according to the invention is to
25 allow, following specific tests, an extremely reliable verification of its authenticity.

Another object of the present invention is to provide a security paper that has a competitive production cost, so as to be extremely advantageous also from an economical standpoint.

30 This aim and these and other objects that will become better apparent

hereinafter are achieved by a security paper according to the invention, characterized in that it comprises a first and a second outer layers and at least one intermediate layer that is interposed between said first and second outer layers, the first outer layer being coupled to the intermediate layer so as to form a monolithic body, the intermediate layer having a different coloring with respect to the first and second outer layers.

Conveniently, a security paper according to the invention is characterized in that the monolithic body is stably coupled to the second outer layer.

As an alternative, a security paper according to the invention is characterized in that the second outer layer is detachably coupled to the monolithic body.

More particularly, according to the invention, a security paper is characterized in that the monolithic body is constituted by a multi-layer paper medium, with the layers, different one another, that are coupled in continuous.

According to another aspect, the present invention provides a method for producing a security paper comprising the following operating steps:

- a step for the stable coupling of a first outer layer and an intermediate layer so as to obtain a monolithic body;
- a step for coupling said monolithic body and a second outer layer, said intermediate layer having a coloring that is different from the coloring of said first and second outer layers.

Conveniently, a method for producing security paper according to the invention is characterized in that the stable coupling for obtaining the monolithic body comprises a method for producing a medium composed of plural, even different, layers arranged one over another and wet coupled together.

Brief Description of the Drawings

Further characteristics and advantages of the invention will become

better apparent from the description of some preferred but not exclusive embodiments of a security paper and of a method for producing it according to the invention, illustrated by way of non-limiting example in the accompanying drawings, wherein:

5 Figure 1 is a perspective view of a portion of a security paper according to a first embodiment;

 Figure 2 is a view of a different embodiment of a security paper according to the invention;

 Figure 3 is a perspective view of an identification label for food
10 products, obtained from a security paper according to the present invention;

 Figure 4 is a perspective view of a security paper, showing the graphic elements that are visible in transmitted light;

 Figure 5 is an enlarged-scale perspective view of a security paper according to the invention;

15 Figure 6 is a diagram of the main steps for the production of a security paper according to the invention; and

 Figure 7 is a diagram, similar to Figure 6, for the production of an adhesive security paper, also according to the invention.

Ways of carrying out the Invention

20 In the examples of embodiments that follow, individual characteristics, given in relation to specific examples, may actually be interchanged with other different characteristics that exist in other examples of embodiments.

 Moreover, it is noted that anything found to be already known during
25 the patenting process is understood not to be claimed and to be the subject of a disclaimer.

 With reference to the figures, and particularly to Figures 1 to 5, a security paper according to the invention, generally designated by the reference numeral 1, is constituted by a first outer layer 2a, a second outer
30 layer 2b, and at least one intermediate layer 3, which during use is

interposed between the first outer layer 2a and the second outer layer 2b.

In particular, according to the invention, the first outer layer 2a is coupled to the intermediate layer 3 in order to form a monolithic body 4.

This coupling, which can be defined as a stable coupling, between the first outer layer 2a and the intermediate layer 3 can be obtained by known methods, such as for example pasting.

However, according to a preferred embodiment, the monolithic body 4 is constituted by a plurality of fibrous layers, even different one another, coupled with a wet process, on a continuous machine.

Such medium is constituted by a two-layer element that is produced directly along the paper production line instead of by coupling two individual layers.

The layers of paper (which in this case have different colors) are pressed together while they are still in pulp form and the drained water of each individual layer is collected separately to ensure high cleanliness of the individual layers.

This method allows to obtain a monolithic body 4 in which the first outer layer 2a and the intermediate layer 3 can however be identified easily; a laboratory analysis, however, allows to check whether the stable coupling is obtained outside the machine or by the wet method on the continuous machine.

Also according to the invention, the intermediate layer 3 has a different coloring with respect to the first outer layer 2a and the second outer layer 2b.

According to a first embodiment, shown in Figure 1, the second outer layer 2b is also coupled stably, for example by pasting, to the monolithic body 4. In this regard, in order to obtain a satisfactory result it is possible to interpose a layer of adhesive during the process for producing the security paper 1 (which will be thoroughly described hereinafter).

According to a different embodiment, the second outer layer 2b can

be detachably coupled to said monolithic body so as to obtain, for example, an adhesive medium such as a true adhesive label.

In this last case, it is possible to provide a layer of silicone material to be interposed between the layer of adhesive and the second outer layer 2b.

5 Also according to the invention, a security paper 1 can have at least one graphic identification element 5 that is visible in transmitted light.

In particular, said graphic identification element 5 can be advantageously obtained by printing, which is performed by using per se known printing devices, at the face 6 of the monolithic body 4 that is
10 directed toward the second outer layer 2b (and is therefore designed to be coupled to the second outer layer 2b).

Conveniently, in order to allow immediate viewing of the graphic identification element 5, the first outer layer 2a and the second outer layer 2b are not completely opaque.

15 Also according to the invention, in order to allow to imprint on the security paper 1 the identification data of the food product (for example by printing a bar code 7), at least one layer between the first outer layer 2a and the second outer layer 2b can be printed for example by laser or ink printing, inkjet printing, direct or indirect thermal transfer printing, and more
20 generally by any more or less traditional printing systems.

According to another aspect, and with particular reference to the diagram shown in Figure 6, the present invention provides a method for producing a security paper 1, comprising the following operating steps:

- a step 101 for the stable coupling of a first outer layer 2a to an
25 intermediate layer 3 in order to obtain a monolithic body 4;
- a step 102 for coupling the monolithic body 4 and a second outer layer 2b one another.

As clearly described earlier, the intermediate layer 3 has a different coloring with respect to the first outer layer 2a and the second outer layer
30 2b.

In particular, step 101 for stable coupling to obtain the monolithic body 4 is achieved by means of a known method for producing a medium composed of a plurality of fibrous layers, as previously defined (see for example page 4), which constitutes the monolithic body 4.

5 Advantageously, the step 102 for coupling the monolithic body 4 (first roll 105) and the second outer layer 2b (second roll 106) one another is performed by means of a step 102a for coating with adhesive said monolithic body 4 at its surface (or face 6) that is intended to be coupled to the second outer layer 2b and by means of the simultaneous passage of the
10 adhesive-coated monolithic body 4 and of the second outer layer 2b through at least one coupling calender 102b.

Again with reference to Figure 6, the method 100 for producing security paper 1 according to the invention can have, prior to the adhesive coating step 102a, a step 103 for printing at least one graphic identification
15 element 5 at the surface (the face 6) of the individual body 4 that is intended to be coupled to the second outer layer 2b.

Furthermore, according to a preferred method, a first drying tunnel 107 can be provided between the printing step 103 and the adhesive coating step 102a, while a second tunnel 108 for drying the adhesive layer can be
20 provided likewise between the adhesive coating step 102a and the coupling step 102b.

Advantageously, downstream of the coupling calender 102 a rehumidification unit 109 is provided.

It is possible to provide for a variation of the present method 100, shown in Figure 7, between the monolithic body 4, on which the graphic
25 identification elements 5 have been optionally printed (second roll 6) and the second outer layer 2b (first roll 105).

In this case, upstream of the adhesive coating step 102a (of the second outer layer 2b) there is a station 110 for siliconizing the surface of
30 the second layer 2b that is designed to be subsequently coupled to the

monolithic body 4.

As in the method described earlier, in this case also, the coupling between the monolithic body 4 and the second outer layer 2b occurs at a coupling calender 102b, and during the coupling step the layer of adhesive
5 is transferred from the second outer layer 2b to the face 6 of the monolithic body 4.

The operation of a security paper particularly but not exclusively suitable for marking food products according to the invention is evident from what has been described above.

10 In particular, it is possible to print on the security paper 1 an identification code (constituted for example by a bar code 7) that is capable of allowing at all times identification of the history of the product to which such code refers.

Merely by way of example, in the case of seafood, it is possible to fix,
15 for example by means of a tamper-evident fixing stud, the security paper to the gill of the fish.

If one wishes to verify the authenticity of the security paper 1 associated with the food product, it is possible to verify first of all whether the graphic identification element 6 visible in transmitted light (against the
20 light) is present or not, and secondly it is possible to tear the security paper 1 to see whether the intermediate layer 3, of a different color with respect to the two outer layers 2a and 2b, is present.

However, if doubts remain regarding the authenticity of the security paper 1, it is possible, by means of a laboratory test, to check whether the
25 monolithic body 4 is actually constituted by a wire-and-drum medium.

The investment required to obtain a wire-and-drum medium is in fact very high and the industrial organizations capable of producing such a medium are numerically very few and in any case identifiable.

All the characteristics of the invention designated above as
30 advantageous, convenient or the like may also be omitted or be replaced

with equivalents.

The invention thus conceived is susceptible of numerous modifications and variations, all of which are within the scope of the appended claims.

5 Thus, for example, the security paper 1 can be covered by a layer of varnish or by a layer of polymeric material to prevent factors such as for example humidity from compromising its appearance and functionality.

10 According to another embodiment, which is conceptually similar, the first and second outer layers 2a and 2b themselves can be made of optionally printable polymeric material, such as polypropylene.

Another possible solution provides a security paper 1 in which two or more intermediate layers 3 are inserted between the first outer layer 2a and the second outer layer 2b in order to increase the degree of safety.

15 In practice it has been found that the security paper thus described can ensure the possibility to verify its authenticity by direct or indirect inspection.

Moreover, it has been demonstrated that the invention has achieved the intended aim and objects in all its embodiments.

20 In practice, the materials used, so long as they are compatible with the contingent use, as well as the dimensions and shapes, may be any according to requirements.

All the details may further be replaced with other technically equivalent elements.

25 The disclosures in Italian Patent Application No. VR2003A000079 from which this application claims priority are incorporated herein by reference.

CLAIMS

1. A security paper, characterized in that it comprises a first and a second outer layers and at least one intermediate layer that is interposed between said first and second outer layers, said first outer layer being
5 coupled to said at least one intermediate layer so as to form a monolithic body, said at least one intermediate layer having a different coloring with respect to said first and second outer layers.

2. The security paper according to claim 1, characterized in that said monolithic body is stably coupled to said second outer layer.

10 3. The security paper according to claims 1 and 2, characterized in that it comprises a layer of adhesive that is interposed between said monolithic body and said second outer layer.

4. The security paper according to claim 1, characterized in that said second outer layer is detachably coupled to said monolithic body.

15 5. The security paper according to one or more of the preceding claims, characterized in that it comprises a layer of silicone material and a layer of adhesive interposed between said second outer layer and said monolithic body.

20 6. The security paper according to one or more of the preceding claims, characterized in that said monolithic body comprises a paper medium composed of a plurality of fibrous layers, coupled by a wet process.

7. The security paper according to one or more of the preceding claims, characterized in that it comprises at least one graphic identification element that is visible in transmitted light.

25 8. The security paper according to one or more of the preceding claims, characterized in that said graphic identification element is printed at the face of said at least one intermediate layer that is directed toward said second outer layer.

30 9. The security paper according to one or more of the preceding claims, characterized in that said first and second outer layers are at least

partially transparent.

10. The security paper according to one or more of the preceding claims, characterized in that said first and/or second layers are printable.

11. A method for producing security paper, characterized in that it
5 comprises the steps of :

-- stably coupling a first outer layer and at least one intermediate layer in order to obtain a monolithic body; and

-- coupling one another said monolithic body and a second outer layer, said
at least one intermediate layer having a coloring that is different from the
10 coloring of said first and second outer layers.

12. The method for producing security paper according to claim 11, characterized in that said stable coupling to obtain a monolithic body comprises steps for producing a medium composed of a plurality of fibrous layers, superimposed and coupled by a wet process.

13. The method for producing security paper according to one or
more of claims 11 and 12, characterized in that said step for coupling said
monolithic body and a second outer layer comprises a step of coating with
adhesive said monolithic body at its surface that is designed to be coupled to
said second outer layer and the simultaneous passage of said adhesive-
20 coated monolithic body and of said second outer layer through at least one
coupling calender.



14. The method for producing security paper according to one or
more of claims 11 and 12, characterized in that said step of coupling said
monolithic body and a second outer layer comprises a step of coating with
25 adhesive said second layer at the surface that is designed to be coupled to
said monolithic body and the simultaneous passage of said adhesive-coated
monolithic body and of said second outer layer through at least one coupling
calender.

15. The method for producing security paper according to one or
30 more of claims 11 to 14, characterized in that it provides, before said step of

coating with adhesive said second outer layer, a step of siliconizing its surface that is designed to be coupled to said monolithic body.

16. The method for producing security paper according to one or more of claims 11 to 15, characterized in that it has, before said adhesive
5 coating step, a step of printing at least one graphic element at the surface of said monolithic body that is designed to be coupled to said second outer layer.

1/4



2/4




Fig. 3




Fig. 4




Fig. 5




Fig. 6

4/4





Fig. 7

INTERNATIONAL SEARCH REPORT

International Application No
 /EP 2004/006430

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 D21H21/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 D21H B32B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99/66127 A (SCAND STICK AB ; FREDIN STEN INGE (SE)) 23 December 1999 (1999-12-23) claims 1-5; figure 4 -----	1-3, 11
X	US 1 910 568 A (SNYDER THEODORE J) 23 May 1933 (1933-05-23) claims 1,2; figures 1-3 -----	1, 11
X	EP 1 254 765 A (RUE DE INT LTD) 6 November 2002 (2002-11-06) claims 1-25; figure 2 -----	1, 11
X	US 5 298 307 A (SUZUKI AKIRA ET AL) 29 March 1994 (1994-03-29) claims 1-13; figures 1-3 ----- -/--	1, 11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

29 September 2004

Date of mailing of the international search report

05/10/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Karlsson, L

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/006430

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 94/16144 A (TEMBOARD INC ; BAIRD BRUCE L (CA); PEPIN MARC (CA)) 21 July 1994 (1994-07-21) claims 1-10; figure 1 -----	1, 11
A	EP 0 453 131 A (JAMES RIVER CORP) 23 October 1991 (1991-10-23) the whole document -----	1-16
A	US 5 161 829 A (DETRICK RICHARD W ET AL) 10 November 1992 (1992-11-10) the whole document -----	1-16
A	EP 0 972 649 A (KANZAN SPEZIALPAPIERE GMBH) 19 January 2000 (2000-01-19) the whole document -----	1-16
A	EP 0 628 408 A (STOJANOVIC BORISLAV ; ANDRIC DRAGISA (YU)) 14 December 1994 (1994-12-14) the whole document -----	1-16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/006430

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9966127	A	23-12-1999	SE 513878 C2 AU 4809399 A EP 1090186 A1 NO 20006364 A SE 9802154 A WO 9966127 A1	20-11-2000 05-01-2000 11-04-2001 02-02-2001 18-12-1999 23-12-1999
US 1910568	A	23-05-1933	NONE	
EP 1254765	A	06-11-2002	GB 2375078 A EP 1254765 A1 US 2002172807 A1	06-11-2002 06-11-2002 21-11-2002
US 5298307	A	29-03-1994	JP 6015794 A JP 8013539 B JP 6040145 A JP 6048070 A CA 2071119 A1 EP 0518363 A1 DE 69216302 D1 DE 69216302 T2	25-01-1994 14-02-1996 15-02-1994 22-02-1994 15-12-1992 16-12-1992 13-02-1997 24-04-1997
WO 9416144	A	21-07-1994	WO 9416144 A1	21-07-1994
EP 0453131	A	23-10-1991	BR 9101477 A CA 2040298 A1 EP 0453131 A2 JP 4222297 A US 5161829 A	26-11-1991 13-10-1991 23-10-1991 12-08-1992 10-11-1992
US 5161829	A	10-11-1992	BR 9101477 A CA 2040298 A1 EP 0453131 A2 JP 4222297 A	26-11-1991 13-10-1991 23-10-1991 12-08-1992
EP 0972649	A	19-01-2000	DE 19832003 A1 AT 252984 T DE 59907509 D1 EP 0972649 A2 ES 2210909 T3	03-02-2000 15-11-2003 04-12-2003 19-01-2000 01-07-2004
EP 0628408	A	14-12-1994	US 5449200 A AT 190554 T AU 680882 B2 AU 6263494 A BG 62390 B1 BG 99482 A BR 9405422 A CA 2102271 A1 CN 1112359 A , B CN 1254777 A , B CN 1257787 A , B CZ 9500582 A3 CZ 9801256 A3 CZ 9801257 A3 DE 69328085 D1 DE 69328085 T2 DK 628408 T3	12-09-1995 15-04-2000 14-08-1997 03-01-1995 29-10-1999 31-01-1996 08-09-1999 09-12-1994 22-11-1995 31-05-2000 28-06-2000 13-09-1995 16-06-1999 16-06-1999 20-04-2000 16-11-2000 14-08-2000

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

EP/EP2004/006430

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0628408	A	EG 20711 A	29-12-1999
		EP 0628408 A1	14-12-1994
		ES 2145022 T3	01-07-2000
		FI 950529 A	05-04-1995
		HU 69674 A2	28-09-1995
		WO 9429105 A1	22-12-1994
		JP 3164823 B2	14-05-2001
		JP 8501838 T	27-02-1996
		KR 255715 B1	01-05-2000
		NO 950375 A	08-02-1995
		NZ 262767 A	26-03-1996
		PL 307349 A1	15-05-1995
		PL 180127 B1	29-12-2000
		PL 180252 B1	31-01-2001
		PT 628408 T	29-09-2000
		RO 111921 B1	31-03-1997
		RU 2110408 C1	10-05-1998
		SG 52378 A1	28-09-1998
		SK 28995 A3	10-01-1996
		HR 940340 A1	31-08-1996
		SI 9400249 A	28-02-1995
		ZA 9401001 A	14-08-1995

PUB-NO: WO2004113612A1
DOCUMENT-IDENTIFIER: WO 2004113612 A1
TITLE: SECURITY PAPER,
PARTICULARLY FOR
LABELS
PUBN-DATE: December 29, 2004

INVENTOR-INFORMATION:

NAME	COUNTRY
FEDRIGONI, GIUSEPPE	IT

ASSIGNEE-INFORMATION:

NAME	COUNTRY
CARTIERE FEDRIGONI E C S P A	IT
FEDRIGONI GIUSEPPE	IT

APPL-NO: EP2004006430

APPL-DATE: June 15, 2004

PRIORITY-DATA: ITVR20030079A (June 20, 2003)

INT-CL (IPC): D21H021/44

ABSTRACT:

CHG DATE=20050212 STATUS=O>A security paper (1), comprising a first and a second outer layers (2a, 2b) and at least one intermediate layer (3) that is interposed between the first and second outer layers, the first outer layer (2a) being coupled to the intermediate layer (3) so as to form a monolithic body, and the intermediate layer (3) having a different coloring with respect to the first (2a) and second (2b) outer layers.